

## FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or AC cable attached
- Power: 36W sereis
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 100\*44.5\*29.5mm(exclude plug)
- Application: Consumer electronics, Telecom and office equipment



## SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 61347, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

## MODEL LIST:

### 36W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-00050600-S10	100-240VAC	30W	5V	6.0A	C6, C8 or C14
SW-00090400-S10	100-240VAC	36W	9V	4.0A	C6, C8 or C14
SW-00120300-S10	100-240VAC	36W	12V	3.0A	C6, C8 or C14
SW-00150240-S10	100-240VAC	36W	15V	2.4A	C6, C8 or C14
SW-00240150-S10	100-240VAC	36W	24V	1.5A	C6, C8 or C14
SW-00480050-S10	100-240VAC	36W	48V	0.75A	C6, C8 or C14

## Mechanical Diagram:

